

Digital Automatic Tyre Inflator - Model Smart Air 076 WALL MOUNTING TYPE

with Microprocessor based automatic air pressure controller with solenoid controlled nozzle for inflation deflation functions.

Technical Specifications:

Max Input Pressure	150 Psi /10 bar /10.2kg /cm2 for continuous duty.
Max Over Pressure	185 psi /12.7 bar / 13 kg /cm2
Pressure Setting Range	150 psi(0.2-10.3 bar 0.2-10.5 kg/cm2)
Maximum Operating Pressure	145 psi /10 bar /10.2 kg /cm2
Resolution	1 psi
Inflation / deflation accuracy	+/- 0.5% of Full Scale
Sensor	Ceramic-based solid state sensor
Sensor Range	145 psi /10 bar /10.2 kg /cm2
Sensor Accuracy	+/- 0.5% of Full scale
Display	2Nos. Backlit 1" LCDs, each with digit and one each for 'SET PRESSURE' and 'TYRE PRESSURE'
Power requirements	230V +/- 10 %, 50Hz +/- 5% (60w) single phase AC mains
Protection Class	IP-65 (Water and dust proof)
Dimensions (in mm)	266.7 (H) x 101.6 (L) x304.8(W)
Weight Net	5.5 Kg approx (Without house)
Weight (packed)	7.0 kg approx. (With house)
Wireless Remote	(Optional)



Tyre inflator for oil companies

HPCL



IOCL



NAYARA



BPCL

